



Amcom™ III communicator



Ordering information

Amcom III Portable rechargeable communicator with internal charger, 2830A/24

T.99.04889

Amcom III Rack Mount communicator, 2830R/24

T.99.01526

The Amcom™ III Series 2830 has all of the same features of our Amcom™ II Series Communicators. These superior communicators utilize separate volume controls for each diver and the tender, both for the uplink and downlink paths.

Features

- Volume setting for each diver and tender to their individual comfort level
- Divers can be set up on 4-Wire Mode or 2-Wire Mode or any combination of the two modes
- Ability to use both dynamic and pre-amplified diver microphones with a unique circuit that detects microphone type and automatically adjusts volume levels
- Weatherproof panel microphone for greater voice intelligibility
- Communicator can be left on charge indefinitely without damage to the batteries or communicator

- Communicator can be operated directly from the charger where AC power is available
- Enough audio power to support three divers

Specifications

- Audio Power Output: 20 Watts per channel
- Frequency Response: 500 Hz to 3 kHz
- Isolation Transformer: Split Bobbin Medical Grade
- Dimensions portable unit 2830A: HxWxD = 10" x 9" x 14.5" (25.4 cm x 22.9 cm x 36.8 cm)
Dimensions rack mount unit 2830R: HxWxD = 7" x 19" x 12.5" (17.8 cm x 48.25 cm x 31.75 cm)
- Weight 2930A: 22 lbs (9.98 kg)
Weight 2930R: 19.5 lbs (8.8 kg)
- Power: 90-264 VAC, 47-440 Hz (automatic sensing), or Internal/External Batteries 12 VDC

V-E

All rights reserved. Reproduction in any form or by any means is not allowed, without prior permission in writing from IHC Hytech BV

IHC Hytech BV

Ramgatseweg 27, 4941 VN, Raamsdonksveer
The Netherlands

T +31 88 015 36 00

hytech@royalihc.com
www.royalihc.com
www.ihchytech.com

The technology innovator.